

11/11/2015 ALL IDEAS, DESIGNS AND ARRANGEMENTS INDICATED ON THESE DRAWINGS ARE THE PROPERTY OF THE ARCHITECT AND ARE TO BE USED IN CONNECTION WITH THIS SPECIFIC PROJECT AND SHALL NOT BE USED OTHERWISE WITHOUT THE EXPRESSED CONSENT OF THE ARCHITECT. THERE SHALL BE NO CHANGES OR DEVIATION FROM THE DRAWINGS OR ACCOMPANYING SPECIFICATION WITHOUT THE EXPRESSED CONSENT OF THE ARCHITECT.

LIGHTING FIXTURE SCHEDULE - CP3

TYPE	DESCRIPTION	MANUFACTURER	LAMP	WATTS	SHIELDED LUMENS	UNSHIELDED LUMENS	VOLTAGE	LOAD TYPE	LOCATION	NOTES
LT-107	PENDANT MOUNTED DECORATIVE FIXTURE	PER INTERIOR DESIGNER	INCANDESCENT	180			120	LINE VOLTAGE	RESTAURANT - HOSTESS STAND	
LT-110	PENDANT MOUNTED DECORATIVE FIXTURE	PER INTERIOR DESIGNER	INCANDESCENT	240			120	LINE VOLTAGE	MAIN BUILDING - RESTROOMS	
LT-111	PENDANT MOUNTED DECORATIVE FIXTURE	PER INTERIOR DESIGNER	INCANDESCENT	40			120	LINE VOLTAGE	MAIN BUILDING - RESTROOMS	
LT-XXX	WALL MOUNTED DECORATIVE SCONCE	PER INTERIOR DESIGNER	INCANDESCENT	50			120	LINE VOLTAGE	EVENT CENTER BALLROOM	
AA1a	EXTERIOR RATED GROUND MOUNTED LED SPOTLIGHT WITH 45 DEG GLARE SHIELD. FIXTURE TO BE MOUNTED TO CONCRETE PAD MINIMUM 2" ABOVE EARTH.	COLOR KINETICS EW BURST COMPACT POWERCORE 523-000059-02 - ARCHITECTURAL FINISH: GRAY ACCESSORIES: 45DEG GLARE SHIELD - 120-000103-04	LED INCLUDED 2700 KELVIN	15	624 LUMENS	N/A	120	LINE VOLTAGE	TALL PALM TREES AT ENTRY	QTY: 12
AA1b	EXTERIOR RATED GROUND MOUNTED ARCHITECTURAL LED SPOTLIGHT WITH 45 DEG GLARE SHIELD. FIXTURE TO BE MOUNTED TO CONCRETE PAD MINIMUM 2" ABOVE EARTH.	COLOR KINETICS EW BURST COMPACT POWERCORE 523-000059-03 - ARCHITECTURAL FINISH: GRAY ACCESSORIES: 45DEG GLARE SHIELD - 120-000103-04	LED INCLUDED 4000 KELVIN	15	812 LUMENS	N/A	120	LINE VOLTAGE	PINES	QTY: 2
AA2	EXTERIOR RATED STAKE MOUNTED ADJUSTABLE LED ACCENT LIGHT WITH FIXED HOOD GLARE SHIELD TO BE MOUNTED TO CONCRETE PAD 2" ABOVE EARTH	KIM LIGHTING EL218F5/8L3KUV-DB FINISH: DARK BRONZE ACCESSORIES: CUSTOM FULL GLARE SHIELD	LED INCLUDED 3000K 35 DEG NFL	16	952 LUMENS	N/A	120-277	LINE VOLTAGE	SITE-TREES GENERAL	QTY: 49
AA3	EXTERIOR RATED STAKE MOUNTED ADJUSTABLE LED ACCENT LIGHT WITH FIXED HOOD GLARE SHIELD TO BE MOUNTED TO CONCRETE PAD 2" ABOVE EARTH	KIM LIGHTING EL218F3/8L3KUV-DB FINISH: DARK BRONZE ACCESSORIES: CUSTOM FULL GLARE SHIELD	LED INCLUDED 3000K 35 DEG NFL	10	651 LUMENS	N/A	120-277	LINE VOLTAGE	SILLOUETTE LIGHTING	QTY: 21
AA4	GROUND MOUNTED EXTERIOR RATED LED PATTERN SPOTLIGHT WITH TWO METAL PATTERNS. FIXTURE TO BE MOUNTED TO CONCRETE PAD MINIMUM 2" ABOVE EARTH.	BEACHSIDE LIGHTING L-011-P-120V-8W-SP-CUSTOM-GS2-SA GOBO PATTERN: TBD PRICE FOR (2) PATTERNS MOUNTING: GS2 HEAVY DUTY GROUND SPIKE; SA SURE AIM LOCKING ROTATION	LED INCLUDED 3000 KELVIN 10 DEG	8	N/A	NO LUMENS LISTED	120	LINE VOLTAGE	PATTERN EFFECTS ON CASITA WALLS	QTY: 9
AA5a	WET LISTED LED ADJUSTABLE SPOTLIGHTS WITH GLARE SHIELD, SPREAD LENS, AND TREE STRAP MOUNTING	CORE LIGHTING (2 FOCUSED UP) FL401-BZ-SAG (2 FOCUSED DOWN) FL401-BZ-SAG-L2 FINISH: BRONZE ACCESSORIES: ANGLED GLARE SHIELD; SPREAD LENS; ROSCO LUX17 COLOR FILTER; MB-100 TREE MOUNTING CANOPY	LED RETROFIT GE LED7XDMR16827/25 2700 KELVIN	7	NO LUMENS LISTED	N/A	120	LINE VOLTAGE	POOL PALM TREE ACCENT LIGHTS	QTY: 40
AA5b	TREE STRAP MOUNTING ACCESSORY	CORE LIGHTING	N/A	N/A	N/A	N/A	N/A		POOL PALM TREES	QTY: 10 CONTRACTOR TO VERIFY DIAMETER OF PALM TRUNK PRIOR TO ORDERING TREE STRAP
AA6	EXTERIOR RATED STAKE MOUNTED ADJUSTABLE LED ACCENT LIGHT WITH FIXED HOOD GLARE SHIELD TO BE MOUNTED TO CONCRETE PAD 2" ABOVE EARTH	KIM LIGHTING EL218F5/8L3KUV-DB FINISH: DARK BRONZE ACCESSORIES: CUSTOM FULL GLARE SHIELD	LED INCLUDED 3000K 35DEG NFL	16	952 LUMENS	N/A	120-277	LINE VOLTAGE	SITE - CACTUS	QTY: 8
AA7	EXTERIOR RATED STAKE MOUNTED ADJUSTABLE LED ACCENT LIGHT WITH FIXED HOOD GLARE SHIELD TO BE MOUNTED TO CONCRETE PAD 2" ABOVE EARTH	KIM LIGHTING EL218S3/8L3KUV-DB FINISH: DARK BRONZE ACCESSORIES: CUSTOM FULL GLARE SHIELD	LED INCLUDED 3000K 15DEG SP	10	927 LUMENS	N/A	120-277	LINE VOLTAGE	SITE WAY-FINDING SIGNAGE POTS	QTY: 19
AA8	EXTERIOR RATED STAKE MOUNTED ADJUSTABLE LED ACCENT LIGHT WITH FIXED HOOD GLARE SHIELD TO BE MOUNTED TO CONCRETE PAD 2" ABOVE EARTH	KIM LIGHTING EL218S5/8L4KUV-DB FINISH: DARK BRONZE ACCESSORIES: CUSTOM FULL GLARE SHIELD	LED INCLUDED 4000K 15DEG SP	16	1772 LUMENS	N/A	120-277	LINE VOLTAGE	HEDGE WALL	QTY: 15
BB1a	EXTERIOR RATED LOW LEVEL 36" LED BOLLARD. FIXTURE TO BE MOUNTED TO CONCRETE PAD MINIMUM 2" ABOVE EARTH.	COOPER LUMIERE EON 303-B1-LEDB2-3000-UNV-T2-BZ-36 BEAM: LATERAL THROW FINISH: BRONZE HEIGHT: 36"	LED INCLUDED 3000 KELVIN	15.5	1300 LUMENS	N/A	120	LINE VOLTAGE	PERIMETER DRIVEWAY	QTY: 70
BB1b	EXTERIOR RATED LOW LEVEL 24" LED BOLLARD. FIXTURE TO BE MOUNTED TO CONCRETE PAD MINIMUM 2" ABOVE EARTH.	COOPER LUMIERE EON 303-B1-LEDB2-3000-UNV-T4-BZ-24 BEAM: LATERAL THROW FINISH: BRONZE HEIGHT: 24"	LED INCLUDED 3000 KELVIN	15.5	1241 LUMENS	N/A	120	LINE VOLTAGE	INTERIOR PATHS AT BRIDGES	QTY: 118
BB2	EXTERIOR RATED LOW LEVEL PATHWAY LIGHT WITH LED RETROFIT LAMP AND STEEL STAKE MOUNTING. FIXTURE TO BE MOUNTED TO CONCRETE PAD MINIMUM 2" ABOVE EARTH.	RAB LL322B FINISH: BLACK	LED RETROFIT CREE BA19-08027OMN-12DE 26-2U100 2700K		75WMAX	NO LUMENS LISTED	120	LINE VOLTAGE	INTERIOR PATHS	QTY: 500 APPROX. LAMP WATTAGE 13.5W
BB3a	NOT USED									
BB3b	NOT USED									



THIS DRAWING RELATES TO LIGHTING DESIGN INTENT ONLY. THE RUZIKA COMPANY DOES NOT ASSUME RESPONSIBILITY FOR STRUCTURAL INTEGRITY, BUILDING, RECORD, CONSTRUCTION, FABRICATION, MATERIAL, OR EQUIPMENT.
THE RUZIKA COMPANY WILL NOT BE HELD RESPONSIBLE FOR THE ABILITY OF CONTRACTORS OR BUILDERS TO EXECUTE THE DESIGN PLANS.
ALL ELECTRICAL INFORMATION AND LOCAL ENERGY CODE COMPLIANCE FORMS TO BE PROVIDED BY A LICENSED ELECTRICAL CONTRACTOR.
ALL EQUIPMENT ATTACHMENT DETAILS AND STRUCTURAL LOAD CALCULATIONS MUST BE PROVIDED BY A LICENSED STRUCTURAL ENGINEER.
FOR LIGHTING DESIGN INFORMATION ONLY

**COTTONWOODS
RESORT & SUITES**
6160 NORTH SCOTTSDALE RD
PARADISE VALLEY AZ

PROJECT NO. 14192

REV. NO.	DATE ISSUED	REASON
13	11/11/15	ASFG SITE LIGHTING REVISIONS

PERMIT SUBMITTAL - CP-3
JUNE 17, 2015

Sheet Title
**LIGHTING
FIXTURE
SCHEDULE**

Sheet No.
LT006-03

11/11/2015 ALL IDEAS, DESIGNS AND ARRANGEMENTS INDICATED ON THESE DRAWINGS ARE THE PROPERTY OF THE ARCHITECT AND ARE TO BE USED IN CONNECTION WITH THIS SPECIFIC PROJECT AND SHALL NOT BE USED OTHERWISE WITHOUT THE EXPRESSED CONSENT OF THE ARCHITECT. THERE SHALL BE NO CHANGES OR DEVIATION FROM THE DRAWINGS OR ACCOMPANYING SPECIFICATION WITHOUT THE EXPRESSED CONSENT OF THE ARCHITECT.

LIGHTING FIXTURE SCHEDULE - CP3										
TYPE	DESCRIPTION	MANUFACTURER	LAMP	WATTS	SHIELDED LUMENS	UNSHIELDED LUMENS	VOLTAGE	LOAD TYPE	LOCATION	NOTES
BB3c	NOT USED									
BB4	EXTERIOR RATED DECORATIVE PATH MARKER LIGHT. FIXTURE TO BE MOUNTED OR PLACED ON CONCRETE PAD MINIMUM 2" ABOVE EARTH.	FIXTURE TBD	LED	25	N/A	N/A	120	LINE VOLTAGE	FRONT ENTRY DRIVEWAY	QTY: 8
DD1	RECESSED WET LOCATION LISTED LED DOWNLIGHT WITH SQUARE APERATURE AND SOFTENING LENS	INTENSE IL-DSTR-NC-L1-27-DELV-60 TRIM: STRD302-B-SFW-SB-SL LENS: SANDBLASTED AND SOLITE	LED INCLUDED 2700 KELVIN	13			120	LINE VOLTAGE	PATIO CEILING	
DP1	EXTERIOR RATED DECORATIVE PENDANT FIXTURE WILL LIKELY REQUIRE 12 VOLT TRANSFORMER. ALL CONDUIT RUN TO FIXTURE TO BE CLEANLY MOUNTED TO TRUNK OF TREE AND SHALL MATCH TRUNK COLOR.	FOSCARINI HAVANA PENDANT MOUNTED	GE FLE13HT3/2/SW/CD 2700K	13	N/A	N/A	120	LINE VOLTAGE	TREE SPARKLERS / TRELIS	QTY: 22
DP2	PENDANT MOUNTED LED DOME FIXTURE	BARN LIGHTING THE DISTRICT LED S-SBD12-PC-<FINISH>-<STEM MOUNTING>-<STEM FINISH>-<DOME LENSED LED-2700K 12" SHADE	LED INCLUDED 2700 KELVIN	12	850	N/A	120	LINE VOLTAGE	TRELIS - BLDG 22/23	QTY: 19
DP3	NOT USED									
LL1	SURFACE MOUNTED LOW VOLTAGE SINGLE COLOR WARM WHITE LED LINEAR STRIP LIGHT WITH 45 DEGREE MOUNTING CHANNEL AND REMOTE ACCESSIBLE DIMMABLE MAGNETIC LOW VOLTAGE DRIVER	CALI LIGHTING 1PLB450-UCM-4WDM-LED-2.7K-WET CONTRACTOR TO PROVIDE NECESSARY DIMMABLE MAGNETIC LOW VOLTAGE DRIVERS. VERIFY MAXIMUM WIRE LENGTH TO PREVENT VOLTAGE DROP. VERIFY NECESSARY LENGTHS WITH ID DRAWINGS. PROVIDE ALL NECESSARY FEED CONNECTORS, AND MOUNTING HARDWARE.	LED INLCUDED WARM WHITE 2700 KELVIN	4W/LFT	ESTIMATED 300 LUMENS A FOOT	N/A	120		VALET DESK BRIDGES	
PP1	EXTERIOR RATED COMPACT FLUORESCENT PARKING LOT POLE LIGHT WITH 12 FOOT POLE. FIXTURE TO BE MOUNTED TO CONCRETE PAD MINIMUM 2" ABOVE EARTH.	BEGA 7880P POLE: 0908HR POLE HEIGHT: 9'-8" FINISH: TBD HEIGHT: 12'	GX24q-3 3000 KELVIN	32	FULL SHEILDED	N/A	120	LINE VOLTAGE	PARKING LOTS	QTY: 33
PP2	NOT USED									
PP3	EXTERIOR RATED 12' POLE WITH NO DRILL CAP TOP AND GFCI BOX 6" FROM TOP OF POLE AT BACK. FIXTURE TO BE MOUNTED TO CONCRETE PAD MINIMUM 2" ABOVE EARTH.	LIGMAN APD-RSA-4012-12'-4"-125'-06 BRONZE HEIGHT: 12' GFCI: 6" FROM TOP AT BACK OF POLE FINISH: BRONZE WITH NO DRILL AND CAP TOP WITH DRILLING FOR (2) EYE BOLTS AT 90 DEGREES AND 3" FROM TOP. ALSO PROVIDE HAND HOLE WIRE ACCESS 6" FROM TOP ON BACK OF POLE FOR GFCI BOX.	N/A	N/A	N/A	N/A	120	LINE VOLTAGE	EVENT COURTYARDS FOR FESTOON LIGHTING	QTY: 12
SL1	RECESSED WET LISTED LED STEP LIGHT	BEGA 2382 LED-<FINISH> FINISH: TBD	LED INCLUDED 3000 KELVIN	7.5	155 LUMENS		120	LINE VOLTAGE	STAIRS / RAMPS	QTY: 73
WW1	EXTERIOR RATED 18" WALL MOUNTED LED SIGNAGE AND ENTRY LIGHTING FOR GUESTROOM IDENTIFICATION	HINKLEY CASCADE 1834BZ-LED FINISH: BRONZE HEIGHT: 18"	LED INCLUDED 2700 KELVIN	15	800 LUMENS	N/A	120	LINE VOLTAGE	CASITA MAIN ENTRY	AT THE ENTRANCE TO EVERY CASITA.
WW2	EXTERIOR RATED 15.5" WALL MOUNTED LED AREA LIGHTING FOR GUESTROOM PATIOS	HINKLEY SHELTER 1326KZ-LED FINISH: BRONZE HEIGHT:	LED INCLUDED 2700 KELVIN	5	400 LUMENS	N/A	120	LINE VOLTAGE	CASITA PATIOS	AT THE REAR EXIT TO ALL CASITAS WITH BACK PATIO AREAS. ALSO USED AS EXTRA LIGHT AT CASITAS WITH LARGE FRONT PATIOS. LOCATION HAVE BEEN CALLED OUT ON DRAWINGS.
WW3	EXTERIOR RATED WALL MOUNTED SQUARE DOWNLIGHT SCONCE WITH SOFTENING LENS	WAC LIGHTING WS-W2504-<FINISH> FINISH: TBD	LED INCLUDED 3000 KELVIN	16 PLUS INRUSH FACTOR	750 LUMENS	N/A	120	ELV	AMENITY BUILDINGS	
WW4	SURFACE MOUNTED WET LOCATION LISTED ROUND LED DOWNLIGHT WITH SOFTENING LENS	HK LIGHTING ZXL30-WM-<HOOD TYPE>-<GLARE SHIELD>-120-25W-HKLED-3K-<FINISH> FINISH: TBD	LED INCLUDED 3000 KELVIN	25 PLUS INRUSH FACTOR	NO LUMENS LISTED	N/A	120	LINE VOLTAGE	AMENITY BUILDING TRELIS	FIXTURE, JUNCTION MOUNTING BOX, AND CONDUIT MUST BE INTEGRATED INTO THE TRELIS STRUCTURE. ALL HARDWARE MUST BE PAINTED TO MATCH TRELIS FINISH.
WW5	EXTERIOR RATED WALL MOUNTED SQUARE LED DOWNLIGHT WITH LATERAL DISTRIBUTION	LUMIERE LIGHTING 303-W1-LEDB1-3000K-UNV-T2-WHITE DISTRIBUTION: TYPE II - LATERAL FINISH: WHITE	LED INCLUDED 3000 KELVIN	8.8 PLUS INRUSH FACTOR	588 LUMENS	N/A	120	LINE VOLTAGE	EXTERIOR SERVICE AREAS ICE MACHINES	QTY: 13



THIS DRAWING RELATES TO LIGHTING DESIGN INTENT ONLY. THE RUZIKA COMPANY DOES NOT ASSUME RESPONSIBILITY FOR STRUCTURAL INTEGRITY, BUILDING, RECORD, CONSTRUCTION, FABRICATION, MATERIAL, OR EQUIPMENT.
THE RUZIKA COMPANY WILL NOT BE HELD RESPONSIBLE FOR THE NEARBY OF CONTRACTORS OR BUILDERS TO EXECUTE THE DESIGN PLANS.
ALL ELECTRICAL INFORMATION AND LOCAL ENERGY CODE COMPLIANCE FORMS TO BE PROVIDED BY A LICENSED ELECTRICAL ENGINEER OR ELECTRICAL CONTRACTOR.
ALL EQUIPMENT ATTACHMENT DETAILS AND STRUCTURAL LOAD CALCULATIONS MUST BE PROVIDED BY A LICENSED STRUCTURAL ENGINEER.
FOR LIGHTING DESIGN INFORMATION ONLY

**COTTONWOODS
RESORT & SUITES**
6160 NORTH SCOTTSDALE RD
PARADISE VALLEY AZ

PROJECT NO. 14192

REV. NO.	DATE ISSUED	REASON
13	11/11/15	ASFG SITE LIGHTING REVISIONS

PERMIT SUBMITTAL - CP-3
JUNE 17, 2015

Sheet Title
**LIGHTING
FIXTURE
SCHEDULE**

Sheet No.
LT007-03