

powered by

**Q.ANTUM**

# Q.PEAK-G4.1 300-305

## Q.ANTUM SOLAR MODULE

The new high-performance module **Q.PEAK-G4.1** is the ideal solution for all applications thanks to its innovative cell technology **Q.ANTUM**. The world-record cell design was developed to achieve the best performance under real conditions – even with low radiation intensity and on clear, hot summer days.



### LOW ELECTRICITY GENERATION COSTS

Higher yield per surface area, lower BOS costs, higher power classes, and an efficiency rate of up to 18.6 %.



### INNOVATIVE ALL-WEATHER TECHNOLOGY

Optimal yields, whatever the weather with excellent low-light and temperature behavior.



### ENDURING HIGH PERFORMANCE

Long-term yield security with Anti LID technology, Anti PID Technology<sup>1</sup>, Hot-Spot Protect and Traceable Quality Tra.Q™.



### EXTREME WEATHER RATING

High-tech aluminum alloy frame, certified for high snow (5400 Pa) and wind loads (4000 Pa) regarding IEC.



### MAXIMUM COST REDUCTIONS

Up to 10 % lower logistics costs due to higher module capacity per box.



### A RELIABLE INVESTMENT

Inclusive 12-year product warranty and 25-year linear performance guarantee<sup>2</sup>.



### THE IDEAL SOLUTION FOR:



Rooftop arrays on residential buildings

Engineered in **Germany**


<sup>1</sup> APT test conditions: Cells at -1500V against grounded, with conductive metal foil covered module surface, 25 °C, 168h

<sup>2</sup> See data sheet on rear for further information.

**Q CELLS**

## MECHANICAL SPECIFICATION

<b>Format</b>	65.7 in × 39.4 in × 1.26 in (including frame) (1670 mm × 1000 mm × 32 mm)
<b>Weight</b>	41.45 lbs (18.8 kg)
<b>Front Cover</b>	0.13 in (3.2 mm) thermally pre-stressed glass with anti-reflection technology
<b>Back Cover</b>	Composite film
<b>Frame</b>	Black anodised aluminum
<b>Cell</b>	6 × 10 monocrystalline Q.ANTUM solar cells
<b>Junction box</b>	2.60-3.03 in × 3.54-4.53 in × 0.59-0.75 in (66-77 mm × 90-115 mm × 15-19 mm), Protection class IP67, with bypass diodes
<b>Cable</b>	4 mm <sup>2</sup> Solar cable; (+) ≥ 39.37 in (1000 mm), (-) ≥ 39.37 in (1000 mm)
<b>Connector</b>	Multi-Contact MC4 or MC4 intermateable, IP68



## ELECTRICAL CHARACTERISTICS

POWER CLASS				300	305
MINIMUM PERFORMANCE AT STANDARD TEST CONDITIONS, STC <sup>1</sup> (POWER TOLERANCE +5 W / -0 W)					
Minimum	Power at MPP <sup>2</sup>	P <sub>MPP</sub>	[W]	300	305
	Short Circuit Current*	I <sub>SC</sub>	[A]	9.77	9.84
	Open Circuit Voltage*	V <sub>OC</sub>	[V]	39.76	40.05
	Current at MPP*	I <sub>MPP</sub>	[A]	9.26	9.35
	Voltage at MPP*	V <sub>MPP</sub>	[V]	32.41	32.62
	Efficiency <sup>2</sup>	η	[%]	≥ 18.0	≥ 18.3
MINIMUM PERFORMANCE AT NORMAL OPERATING CONDITIONS, NOC <sup>3</sup>					
Minimum	Power at MPP <sup>2</sup>	P <sub>MPP</sub>	[W]	222.0	225.7
	Short Circuit Current*	I <sub>SC</sub>	[A]	7.88	7.94
	Open Circuit Voltage*	V <sub>OC</sub>	[V]	37.19	37.46
	Current at MPP*	I <sub>MPP</sub>	[A]	7.27	7.35
	Voltage at MPP*	V <sub>MPP</sub>	[V]	30.52	30.70


<sup>1</sup> 1000 W/m<sup>2</sup>, 25 °C, spectrum AM 1.5 G

<sup>2</sup> Measurement tolerances STC ± 3 %; NOC ± 5 %

<sup>3</sup> 800 W/m<sup>2</sup>, NOCT, spectrum AM 1.5 G

\* typical values, actual values may differ


### Q CELLS PERFORMANCE WARRANTY



At least 98 % of nominal power during first year.  
Thereafter max. 0.6 % degradation per year.  
At least 92.6 % of nominal power up to 10 years.  
At least 83.6 % of nominal power up to 25 years.

All data within measurement tolerances.  
Full warranties in accordance with the warranty terms of the Q CELLS sales organization of your respective country.

### PERFORMANCE AT LOW IRRADIANCE



Typical module performance under low irradiance conditions in comparison to STC conditions (25 °C, 1000 W/m<sup>2</sup>).

### TEMPERATURE COEFFICIENTS

Temperature Coefficient of I <sub>SC</sub>	α	[%/K]	+0.04	Temperature Coefficient of V <sub>OC</sub>	β	[%/K]	-0.28
Temperature Coefficient of P <sub>MPP</sub>	γ	[%/K]	-0.39	Normal Operating Cell Temperature	NOCT	[°F]	113 ± 5.4 (45 ± 3 °C)

## PROPERTIES FOR SYSTEM DESIGN

Maximum System Voltage V <sub>sys</sub>	[V]	1000 (IEC) / 1000 (UL)	Safety Class	II
Maximum Series Fuse Rating	[A DC]	20	Fire Rating	C (IEC) / TYPE 1 (UL)
Design load, push (UL) <sup>2</sup>	[lbs/ft <sup>2</sup> ]	75 (3600 Pa)	Permitted module temperature on continuous duty	-40 °F up to +185 °F (-40 °C up to +85 °C)
Design load, pull (UL) <sup>2</sup>	[lbs/ft <sup>2</sup> ]	55.6 (2666 Pa)	<sup>2</sup> see installation manual	

## QUALIFICATIONS AND CERTIFICATES

UL 1703; VDE Quality Tested; CE-compliant;  
IEC 61215 (Ed.2); IEC 61730 (Ed.1) application class A



## PACKAGING INFORMATION

Number of Modules per Pallet	32
Number of Pallets per 53' Container	30
Number of Pallets per 40' Container	26
Pallet Dimensions ( L × W × H )	68.7 in × 45.3 in × 46.1 in (1745 mm × 1150 mm × 1170 mm)
Pallet Weight	1435 lbs (651 kg)

**NOTE:** Installation instructions must be followed. See the installation and operating manual or contact our technical service department for further information on approved installation and use of this product.

Hanwha Q CELLS America Inc.

300 Spectrum Center Drive, Suite 1250, Irvine, CA 92618, USA | TEL +1 949 748 59 96 | EMAIL inquiry@us.q-cells.com | WEB www.q-cells.us